

MB s1700 ASRock Z790 PG LIGHTNING 90-MXBKA0-A0UAYZ

Šifra: 20153

Kategorija proizvoda: Matične ploče

Proizvođač: ASROCK

Cena: **18.994,00** rsd.

CPU

- Supports 13th Gen & 12th Gen Intel® Core™ Processors (LGA1700)
- Supports Intel® Hybrid Technology
- Supports Intel® Turbo Boost Max 3.0 Technology
- Supports Intel® Thermal Velocity Boost (TVB)
- Supports Intel® Adaptive Boost Technology (ABT)

Chipset

- Intel® Z790

BIOS

- 128Mb AMI UEFI Legal BIOS with GUI support

Audio

- 7.1 CH HD Audio (Realtek ALC897 Audio Codec)
- Nahimic Audio

Slots

CPU:

- 1 x PCIe 5.0 x16 Slot (PCIe1), supports x16 mode*

Chipset:

- 1 x PCIe 4.0 x16 Slot (PCIe4), supports x4 mode*
- 3 x PCIe 3.0 x1 Slots (PCIe2, PCIe3 and PCIe5)*
- 1 x M.2 Socket (Key E), supports type 2230 WiFi/BT



Memor

- Dual Channel
- 4 x DDR5 Slots
- Supports Intel® 7200+ Series
- Max. 128GB
- Supports ECC

Graphi

- Intel® Arc™ A770 Graphics
- 1 x DPC 2.1
- 1 x eDP 1.2
- 2 x DPC 1.2
- 60Hz 2
- 2 DPC 2
- 1 x HDMI
- and more

*Intel® outputs are GPU

LAN

- 2.5 GbE LAN
- Dragon
- Supports
- Smart
- Visual
- Visual
- Optim
- Stream
- User

PCIe WiFi module and Intel® CNVio/CNVio2 (Integrated WiFi/BT)

- Supports AMD CrossFire™

*Supports NVMe SSD as boot disks

Storage

CPU:

- 1 x Hyper M.2 Socket (M2_1, Key M), supports type 2260/2280 PCIe Gen4x4 (64 Gb/s) mode*

Chipset:

- 1 x Hyper M.2 Socket (M2_2, Key M), supports type 2242/2260/2280 PCIe Gen4x4 (64 Gb/s) mode*

- 1 x Hyper M.2 Socket (M2_3, Key M), supports type 2260/2280 SATA3 6.0 Gb/s & PCIe Gen4x4 (64 Gb/s) modes*

- 1 x Hyper M.2 Socket (M2_4, Key M), supports type 2260/2280 PCIe Gen4x4 (64 Gb/s) mode*

- 4 x SATA3 6.0 Gb/s Connectors

*Supports Intel® Volume Management Device (VMD)
Supports NVMe SSD as boot disks

USB

- 1 x USB 3.2 Gen2x2 Type-C (Rear)

- 1 x USB 3.2 Gen2 Type-A (Rear)

- 1 x USB 3.2 Gen1 Type-C (Front)

- 9 x USB 3.2 Gen1 Type-A (5 Rear, 4 Front)

- 3 x USB 2.0 (1 Rear, 2 Front)

*All USB ports support ESD Protection

Rear Panel I/O

- 2 x Antenna Mounting Points

- 1 x PS/2 Mouse/Keyboard Port

- 1 x HDMI Port

- 1 x USB 3.2 Gen2 Type-A Port (10 Gb/s)

- 1 x USB 3.2 Gen2x2 Type-C Port (20 Gb/s)

- 5 x USB 3.2 Gen1 Ports

- 1 x USB 2.0 Port

- 1 x RJ-45 LAN Port

- HD Audio Jacks: Line in / Front Speaker / Microphone

Form Factor

RAID

- Support

storage

- Support

storage

Connect

- 1 x eL

- 1 x SH

- 1 x PC

- 1 x Po

- 3 x Ac

- 1 x Cl

- 1 x Cl

Speake

Softwa

55ftW

(SRD)

- **ASR2**

- **ASR8**

UEFI

- **ASR6**

- **ASR6**

ASR6

ASR6

ASR6

ASR6

ASR6

ASR6

ASR6

ASR6

ASR6

ASR6

ASR6

ASR6

ASR6

ASR6

ASR6

ASR6

ASR6

ASR6

ASR6

ASR6

ASR6

ASR6

ASR6

ASR6

ASR6

ASR6

ASR6

ASR6

ASR6

ASR6

ASR6

ASR6

ASR6

ASR6

ASR6

ASR6

ASR6

ASR6

ASR6

ASR6

