

logo not found or type unknown

Firma: Duocom
Adresa: Dalmatinska 17, Beograd
Telefon: 011/32 94 998, 062/424 870,
062/424 860
Fax: /
PIB: 105926887
E-mail: duocom.rs@gmail.com

MB AM4 ASRock B550M-HDV 90-MXBDJ0-A0UAYZ

Šifra: 20154

Kategorija proizvoda: Matične ploče

Proizvođač: ASROCK

Cena: **8.226,00** rsd.



CPU

- Supports AMD AM4 Socket Ryzen™ 3000, 3000 G-Series, 4000 G-Series, 5000 and 5000 G-Series Desktop Processors*
- 6 Power Phase design

*Not compatible with AMD Athlon™ Processors.

Chipset

- AMD B550

Memor

- Dual Channel DDR4 Memory Technology
- 2 x DDR4 DIMM Slots
- AMD Ryzen series CPUs (Vermeer) support DDR4 4600+(OC) / 4533(OC) / 4466(OC) / 4400(OC) / 4333(OC) / 4333(OC) / 4266(OC) / 4200(OC) / 4133(OC) / 4000(OC) / 3866(OC) / 3800(OC) / 3733(OC) / 3600(OC) / 3466(OC) / 3200 / 2933 / 2667 / 2400 / 2133 ECC & non-ECC, un-buffered memory*
- AMD Ryzen series CPUs (Matisse) support DDR4 4600+(OC) / 4533(OC) / 4466(OC) / 4400(OC) / 4333(OC) / 4333(OC) / 4266(OC) / 4200(OC) / 4133(OC) / 4000(OC) / 3866(OC) / 3800(OC) / 3733(OC) / 3600(OC) / 3466(OC) / 3200 / 2933 / 2667 / 2400 / 2133 ECC & non-ECC, un-buffered memory*
- AMD Ryzen series APUs (Cezanne) support DDR4 4733+(OC) / 4666(OC) / 4600(OC) / 4533(OC) / 4466(OC) / 4400(OC) / 4333(OC) / 4266(OC) / 4200(OC) / 4133(OC) / 4000(OC) / 3866(OC) / 3800(OC) / 3733(OC) / 3600(OC) / 3466(OC) / 3200 / 2933 / 2667 / 2400 / 2133 ECC & non-ECC, un-buffered memory*
- AMD Ryzen series APUs (Renoir) support DDR4 4733+(OC) / 4666(OC) / 4600(OC) / 4533(OC) / 4466(OC) / 4400(OC) / 4333(OC) / 4266(OC) / 4200(OC) / 4133(OC) / 4000(OC) / 3866(OC) / 3800(OC) / 3733(OC) / 3600(OC) / 3466(OC) / 3200 / 2933 / 2667 / 2400 / 2133 ECC & non-ECC, un-buffered memory*
- AMD Ryzen series APUs (Picasso) support DDR4 3533+(OC) / 3466(OC) / 3200(OC) / 2933 / 2667 / 2400 / 2133 non-ECC, un-buffered memory*
- Max. capacity of system memory: 64GB**
- Supports Extreme Memory Profile (XMP) memory modules
- 15µ Gold Contact in DIMM Slots*

SR: Single rank DIMM, 1Rx4 or 1Rx8 on DIMM module label

DR: Dual rank DIMM, 2Rx4 or 2Rx8 on DIMM module label

**Due to the operating system limitation, the actual memory size may be less than 4GB for the reservation for system usage under Windows® 32-bit OS. For Windows® 64-bit OS with 64-bit CPU, there is no such limitation.

BIOS

- 256Mb AMI UEFI Legal BIOS with GUI support
- Supports "Plug and Play"
- ACPI 5.1 compliance wake up events
- Supports jumperfree
- SMBIOS 2.3 support
- CPU, CPU VDDCR_SOC, DRAM, VDDP Voltage Multi-adjustment

- Integrated AMD Radeon Vega Series Graphics in Ryzen Series APU*
- DirectX 12, Pixel Shader 5.0
- Shared memory default 2GB. Max Shared memory supports up to 16GB.**
- Three graphics output options: D-Sub, DVI-D and HDMI
- Supports Triple Monitor
- Supports HDMI 2.1 with max. resolution up to 4K x 2K (4096x2160) @ 60Hz
- Supports DVI-D with max. resolution up to 1920x1200 @ 60Hz
- Supports D-Sub with max. resolution up to 1920x1200 @ 60Hz
- Supports Auto Lip Sync, Deep Color (12bpc), xvYCC and HBR (High Bit Rate Audio) with HDMI 2.1 Port (Compliant HDMI monitor is required)
- Supports HDR (High Dynamic Range) with HDMI 2.1
- Supports HDCP 2.3 with DVI-D and HDMI 2.1 Ports***
- Supports 4K Ultra HD (UHD) playback with HDMI 2.1 Port
- Supports Microsoft® PlayReady

*Actual support may vary by CPU

**The Max shared memory 16GB requires 32GB system memory installed.

***Picasso supports HDCP 2.2 with HDMI 2.0 Port

Audio

- 7.1 CH HD Audio (Realtek ALC887/897 Audio Codec)
- Supports Surge Protection

Slots

AMD Ryzen series CPUs (Vermeer and Matisse)

- 1 x PCI Express 4.0 x16 Slot (PCIe1: x16 mode)*

AMD Ryzen series APUs (Cezanne and Renoir)

- 1 x PCI Express 3.0 x16 Slot (PCIe1: x16 mode)*

AMD Ryzen series APUs (Picasso)

- 1 x PCI Express 3.0 x16 Slot (PCIe1: x8 mode)*

- 1 x PCI Express 3.0 x1 Slot

*Supports NVMe SSD as boot disks

Connector

- 1 x SPI TPM Header
- 1 x COM Port Header
- 1 x Chassis Intrusion and Speaker Header
- 1 x CPU Fan Connector (4-pin)*
- 2 x Chassis Fan Connectors (4-pin) (Smart Fan Speed Control)**
- 1 x 24 pin ATX Power Connector
- 1 x 4 pin 12V Power Connector
- 1 x Front Panel Audio Connector
- 2 x USB 2.0 Headers (Support 4 USB 2.0 ports) (Supports ESD Protection)
- 1 x USB 3.2 Gen1 Header (Supports 2 USB 3.2 Gen1 ports) (Supports ESD Protection)

*The CPU Fan Connector supports the CPU fan of maximum 1A (12W) fan power.

**The Chassis Fan supports the water cooler fan of maximum 1A (12W) fan power. CHA_FAN2 can auto detect if 3-pin or 4-pin fan is in use.

Software and UEFI

Software

- ASRock Motherboard Utility (A-Tuning)
- ASRock XFast LAN

UEFI

- ASRock Full HD UEFI
- ASRock Instant Flash

*These utilities can be downloaded from ASRock Live Update & APP Shop.

LAN

- PCIe x
- Realte
- Suppo
- Suppo
- Suppo
- Suppo

Storage

- 4 x SA
- RAID 1
- 1 x H
- 2242/2
- PCI Exp
- Verme
- Renoir

*Suppo

- Support
- Rear Pa
- 1 x PS
- 1 x D
- 1 x D
- 1 x H
- 2 x U
- 4 x U
- 1 x RJ
- LED)
- HD Au

Support

- Drivers, Utilities, AntiVirus Software (Trial Version),
Google Chrome Browser and Toolbar

Accessories

- Quick Installation Guide, Support CD, I/O Shield
- 2 x SATA Data Cables
- 1 x Screw for M.2 Socket

Form Factor

- Micro ATX Form Factor: 9.0-in x 7.9-in, 23.0 cm x 20.1 cm

Hardwa
- Temp
- Fan T
- Quiet
temper
- Fan M
- CASE
- Volta