

logo not found or type unknown

Firma: Duocom
Adresa: Dalmatinska 17, Beograd
Telefon: 011/32 94 998, 062/424 870,
062/424 860
Fax: /
PIB: 105926887
E-mail: duocom.rs@gmail.com

MB s1700 Gigabyte Z690M DS3H DDR4

Šifra: 5503

Kategorija proizvoda: Matične ploče

Proizvođač: GIGABYTE

Cena: **17.808,00** rsd.



CPU

LGA1700 socket: L3 cache varies with CPU
Support for 12th
Generation Intel®
Core™, Pentium® Gold
and Celeron®
Processors*

Chipset

Intel® Z690 Express
Chipset

Memor

* Please refer to "CPU Support List" for more
information.

Support for DDR4 5333(O.C.)/ DDR4 5133(O.C.)/DDR4 5000(O.C.)/4933(O.C.)/4800(O.C.)/ 4700(O.C.)/ 4600(O.C.)/ 4500(O.C.)/ 4400(O.C.)/ 4300(O.C.)/4266(O.C.) / 4133(O.C.) / 4000(O.C.) / 3866(O.C.) / 3800(O.C.) / 3733(O.C.) / 3666(O.C.) / 3600(O.C.) / 3466(O.C.) / 3400(O.C.) / 3333(O.C.) / 3300(O.C.) / 3200 / 3000 / 2933 / 2800 / 2666 / 2400 / 2133 MHz memory modules	4 x DDR DIMM sockets supporting up to 128 GB (32 GB single DIMM capacity) of system memory	Onboard Graphics Integrated Graphics Processor-Intel® HD Graphics support:	Audio Realtek
	Dual channel memory architecture	1 x D-Sub port, supporting a maximum resolution of 1920x1200@60 Hz	1 x HDMI port, supporting a maximum resolution of 4096x2160@60 Hz * Support for HDMI 2.1 version and HDCP 2.3 ** Support native HDMI resolution of 4096x2304@60 Hz Ports: 1 x DisplayPort, supporting a maximum resolution of 4096x2304@60 Hz * Support for DisplayPort 1.2 version and HDCP 2.3
	Support for ECC Un-buffered DIMM 1Rx8/2Rx8 memory modules (operate in non-ECC mode)		1 x DisplayPort, supporting a maximum resolution of 4096x2304@60 Hz * Support for DisplayPort 1.2 version.
	Support for Extreme Memory Profile (XMP) memory modules	(Graphics specifications may vary depending on CPU support.)	
		Support for up to 4 displays at the same time	
(Go to GIGABYTE's website for the latest supported memory speeds and memory modules.)			
		LAN Realtek® 2.5GbE LAN chip (2.5 Gbps/1 Gbps/100 Mbps)	Expansion 1 x PCIe 4.0 slot running at x4 (The configuration is subject to BIOS and hardware support.)
		Storage Interface CPU: 1 x M.2 connector (Socket 3, M key, type 2260/2280 PCIe 4.0 x4/x2 SSD support) (M2A_CPU) Chipset: 1 x M.2 connector (Socket 3, M key, type 2260/2280 PCIe 4.0 x4/x2 SSD support) (M2P_SB)	4 x SATA 6Gb/s connectors

Support for RAID 0, RAID 1, RAID 5, and RAID 10			
Intel® Optane™ Memory Ready * System acceleration with Intel® Optane™ Memory can only be enabled on the M.2 connector supported by the Chipset.	USB Chipset: 1 x USB Type-C® port on the back panel, with USB 3.2 Gen 2 support	5 x USB 3.2 Gen 1 ports (3 ports on the back panel, 2 ports available through the internal USB header) 2 x USB 2.0/1.1 ports on the back panel	Internal 1 x 2-pin power
	Chipset+2 USB 2.0 Hubs: 4 x USB 2.0/1.1 ports available through the internal USB headers		
	Back Panel Connectors 2 x USB 2.0/1.1 ports	1 x PS/2 keyboard/mouse port 1 x D-Sub port 1 x HDMI 2.0 port 2 x DisplayPorts 3 x USB 3.2 Gen 1 ports 1 x USB Type-C® port, with USB 3.2 Gen 2 support 1 x RJ-45 port 3 x audio jacks	I/O Connector ITE®
			*All fan and high power deliver
	H/W Monitoring Voltage detection	Temperature detection Fan speed detection Fan fail warning Fan speed control * Whether the fan speed control function is supported will depend on the cooler you install.	BIOS

1 x 256 Mbit flash	Use of licensed AMI UEFI BIOS PCI 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0	Unique Features Support for APP Center * Available applications in APP Center may vary by motherboard model. Supported functions of each application may also vary depending on motherboard specifications. @BIOS EasyTune Fast Boot Game Boost ON/OFF Charge RGB Fusion Smart Backup System Information Viewer	Support for Q-Flash Plus	Bundle Norton Security
			Support for Q-Flash Support for Xpress Install	
		Operating System Support for Windows 10 64-bit		Form Factor Micro 24.4cm